* .	•					50X
· Service ·						
•	A Fig. 1. Process					•
ENTRAL IN	TELLIGENCE	AGENCY	\	This Document con	tains information affecting ne United States, within th	the Na-
NFORMAT	ION REPOR	?T		ing of Title 18, Sec amended. Its trans to or receipt by an	tions 793 and 794, of the U.S. mission or revelation of its unauthorized person is pr duction of this form is pr	. Code, as contents cohibited
:		CONFID	ENTIAL	·		
COUNTRY	USSR (Kuyb)	shev Oblast)		REPORT	•	50X
SUBJECT	Experimenta	l Engine Devel	opment at	DATE DISTR.	27 Apr	ril 1954
	Zaved 2, Ku	ybysnev		NO. OF PAG	GES 3	50X1-HUM
DATE OF INFO.			,	REQUIREMENT		
PLACE ACQUIRED				REFERENCES		
				•	· · · · · · · · · · · · · · · · · · ·	50X1-HUM
	THE		F CONTENT IS TELES	NTATIVE.	·	
						50X1-HU
						50X
,						
·						
	· **					
	**************************************					
	**************************************					· .
	<b>85</b> .					· .
	No.					
	No.					
		CONFI	DENTIAL			

* *	•		OCCIPATA NEGURVATOR	REPORT	50X1
	7				50X1-HUN
	N 16 1456.	#+*·· <del>†</del>		DATE DISTR. 19 M/	AR.54
	DUNTRY ;	USSR		NO 05 34 650 2	
SU	BJECT	Experiments Kuybyshev	l Engine Development at Zavod	NO. OF PAGES 2	,
PL	ACE.		• ••	NO. OF ENCLS.	
AC	CQUIRED :		:	(LISTED BELOW)	50X1-HUN
DA AG	TE COUIRED BY	Y SOURCE 1		SUPPLEMENT TO REPORT NO.	
		र प्रकार विकास करें की जिल्हा है। इसके की जिल्हा के किस्ता की		•	
	ATE OF INFO	DÉMATION :	. , , ,	·	
•		<b>,</b>	THIS IS UNEVALUATED INFORMATIO	N	
	٠			•	å ·
	0				50X1-HUN
					•
					,
					,
					. '
					h.
					6
					47.
					E.
					A. X
					A.
					X.
		· · · · · · · · · · · · · · · · · · ·		,	
		Starter 4 %			r.
<u>78:</u> 3.			ch starters were built and	they were	Yr.,
	deliver	su ed to Zavod they m	ch starters were built and 2 in completed form from some ay have come from Bezymyanka.	they were	r.
	deliver	su ed to Zavod they m	ch starters were built and 2 in completed form from some	they were	50X1-HUN
	deliver	su ed to Zavod they m	ch starters were built and 2 in completed form from some ay have come from Bezymyanka.	they were	50X1-HUN
	deliver	su ed to Zavod they m	ch starters were built and 2 in completed form from some ay have come from Bezymyanka.	they were	50X1-HUN
	deliver	su ed to Zavod they m	ch starters were built and 2 in completed form from some ay have come from Bezymyanka.	they were	50X1-HUN
	deliver	su ed to Zavod they m	ch starters were built and 2 in completed form from some ay have come from Bezymyanka.	they were	50X1-HUN

consisted of this project consisted of two engines coupled by a gear box to deliver power to a single-propeller shaft. they had experienced some failures during the testing of the M Project engines and that they had occurred in the gear box connecting the two engines.  They had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had tried a hydro-abrasive process: for police that they had they had the police that they had they had they had they had been run at reduced power.    Turbine and compressor attempt was abradows:
this project this project this project the project of the M Project engines and that these failures that during the testing of the M Project engines and that these failures had occurred in the gear box connecting the two engines.  They had tried a hydro-abrasive process for polishing these gears.  They had tried a hydro-abrasive process for polishing these gears.  The under construction at Zaved 2 but that only one had been completed by June 1955 that only one had been completed by June 1955 that only been run at reduced power.  The mounted on a test stand but had only been run at reduced power.  Soxi-had one part up to speed before starting to turn the other part was started first, and this specials of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were formed in four steps. Three stamping operations produced the compressor blades were
this project  two engines coupled by a gear box to deliver power to a single propellor shaft.  they had experienced some failures had occurred in the gear box connecting the two engines.  they had tried a hydro-abrasive process for polich- ing these gears.  K Project engines and that these failures they had tried a hydro-abrasive process for polich- ing these gears.  K Project engines and that several to this one had been completed by June 1953  been mounted on a test stand but had only been run at reduced power.  The complete of this one had been compressor into two parts and to accelerate the one part up to speed before starting to turn the other part; did not know where the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part; did not know where the compressor was divided or which part was started first, and  this split compressor attempt was accelerating to turn the other part; bendowed was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the second
this project  two engines coupled by a gear box to deliver power to a single  propeller shaft.
this project  two engines coupled by a gear box to deliver power to a single propeller shaft.
this project  two engines coupled by a gear box to deliver power to a single propeller shaft.  they had experienced some failures had occurred in the gear box connecting the two engines had occurred in the gear box connecting the two engines had occurred in the gear box connecting the two engines had occurred in the gear box connecting the two engines had occurred in the gear box connecting the two engines had occurred in the gear box connecting the two engines had occurred in the gear box connecting the two engines  K Project engines and that reseveral*  SOX1-  Were under construction at Zaved 2 but that only one had been completed by June 1953  whis one had been mounted on a test stand but had only been run at reduced power.  SOX1-  SOX1-  Toxicle  In knowledge of any variable angle blading being used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part was started first, and  this split compressor attempt was started first, and  this split compressor attempt was started first, and  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
two engines coupled by a gear box to deliver power to a single propeller shaft.
propeller shaft.   they had experienced some failures during the testing of the M Project engines and that these failures had occurred in the gear box connecting the two engines.   50X1-hing these gears.   50X1-hing the gear gear gear gear.   50X1-hing the gear gear.   50X1-hing the gear gear gear.   50X1-hing the gear gear.
during the testing of the M Project engines and that these failures had occurred in the gear box connecting the two engines.  they had tried a hydro-abrasive process for polishing these gears.  E Project engines and that several this one had completed by June 1953  See mounted on a test stand but had only been run at reduced power.  50X1-been mounted on a test stand but had only been run at reduced power.  50X1-been mounted on a test stand but had only been run at reduced power.  50X1-been mounted on a test stand but had only been run at reduced power.  50X1-been mounted on a test stand but had only been run at reduced power.  50X1-been mounted on a test stand but had only been run at reduced power.  50X1-been mounted on a test stand but had only been run at reduced power.  50X1-been mounted on a test stand but had only been run at reduced power.  50X1-been mounted on a test stand but had only been run at tempt was attacked first, and  this split compressor attempt was attacked first, and  this split compressor attempt was attacked first, and  this split compressor attempt was attacked first, and  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the compressor blades were
they had tried a hydro-abrasive process for polishing these goars.    They had tried a hydro-abrasive process for polishing these goars.   Sox1-type
they had tried a hydro-abrasive process for polishing these goars.    K Project engines and that "several"   50X1-home the construction at Zaved 2 but that only one had been   50X1-home the construction at Zaved 2 but that only one had been   50X1-home mounted on a test stand but had only been run at reduced power.    no knowledge of any variable angle blading teing used in this engine.
R Project engines and that "several" 50X1-  were under construction at Zaved 2 but that only one had been completed by June 1953  been mounted on a test stand but had, only been run at reduced power.  50X1-  50X1
R Project engines and that "several"  were under construction at Zaved 2 but that only one had been completed by June 1953  no knowledge of any variable angle blading being used in this engine.  an attempt was made on one engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part.  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was abandoned;  were because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
R Project engines and that several 50X1-h were under construction at Zaved 2 but that only one had been 50X1-h seen mounted on a test stand but had, only been run at reduced power.  50X1-h 50
no knowledge of any variable angle blading being used in this engine.  an attempt was made on one engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part did not know where the compressor was divided or which part was started first, and  this split compressor attempt was accelerate the mechanism to produce this separate acceleration.  Turbine and compressor bladge were  formed in four steps. Three stamping operations produced the
mo knowledge of any variable angle blading being used in this engine.  an attempt was made on one engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part; attarted first, and  this split compressor attempt was serviced in the gearing this split compressor attempt was serviced in the gearing this split compressor attempt was serviced in the gearing this split compressor blades were formed in four steps. Three stamping operations produced the
no knowledge of any variable angle blading being used in this engine.  an attempt was made on one engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part.  bandoned;  bandoned;  was because of excessive welch in the gearing mechanism to produce this separate acceleration.  Turbine and compressor bladge were  formed in four steps. Three stamping operations produced the  50X1-1-  50X1-1-  50X1-1-  50X1-1-  50X1-1-  Turbine and compressor bladge were
no knowledge of any variable angle blading being used in this engine.  an attempt was made on one engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other parts.  bandonst was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the compressor stamping operations and compressor blades were
no knowledge of any variable angle blading being used in this engine.  an attempt was made on one engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was abandoned;  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
no knowledge of any variable angle blading being used in this engine.  an attempt was made on one engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was abandoned;  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was abandons;  bandons;  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was abandons;  bandons;  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was shandowd;  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was shandowd;  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was shandowd;  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was started first, and  this split compressor attempt was sendencied to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was started first, and  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was started first, and  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
used in this engine.  engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part;  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was started first, and  was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
engine to divide the compressor into two parts and to accelerate the one part up to speed before starting to turn the other part.  did not know where the compressor was divided or which part was started first, and  this split compressor attempt was shandows:  bandows:  bandows:  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
one part up to speed before starting to turn the other part   50X1-  did not know where the compressor was divided or which part was started first, and
did not know where the compressor was divided or which part was started first, and 50X1-l-  this split compressor attempt was a-  bandonsd was because of excessive weight in the gearing mechanism to produce this separate acceleration. 50X1-l-  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
started first, and
this split compressor attempt was a bandoned was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were formed in four steps. Three stamping operations produced the
bandonsh was because of excessive weight in the gearing mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
mechanism to produce this separate acceleration.  Turbine and compressor blades were  formed in four steps. Three stamping operations produced the
formed in four steps. Three stamping operations produced the
formed in four steps. Three stamping operations produced the
OUXI-HU
limisued prade form and then the YIL tree look was out outo and
root end.
FOWAL TOWN
during the development
of the 022 there was some emphasis placed on the reduction of fuel
consumption.
50X1-F
the jigs and fixtures
were for the manufacture of parts for experimental engines, and
although the drawings were sent to another plant, 50X1-
these same jigs would not be practical for series production.
AMOOD GOME 1480 AARTA WAS AS NEGATIONE TAY DON'TO BURNESS NO NEW SEC. 3

CONFIDENTIAL